

BSMW Series

Wall Mounted Low Voltage Lithium Battery



WiFi APP
download:



BASIC PARAMETERS	BSM48100W	BSM48200W
Nominal Voltage (V)	51.2	51.2
Nominal Capacity (KWH)	5.12	10.24
Usable Capacity (KWH)	4.608	9.216
Charge Voltage (V)	56-58.4	56-58.4
Discharge Voltage (V)	40-48	40-48
Battery System Discharge Current (Standard)	50	100
Battery System Discharge Current (Max)	100	200
Peak Charge/Discharge Current(A)	120(2S)	240(2S)
Communication	CAN/RS-485/RS-232	
Working Temperature	0°C~50°C Charge -10°C ~50°C Discharge	
Shelf Temperature	-20°C~45°C	
Certification	CE/IEC/UL/UN38.3/MSDS	
Design Life	10 years+	
Size(mm)	348*598*163	691*605*163
Weight(KGS)	42.1	81.7
Cycle Life ^[1]	>6000	

[1] Test conditions: 0.2C Charging/Discharging,@25°C, 80%DoD

ENERGY STORAGE SOLUTIONS

LiFePO4 chemistry battery with safety performance and longer cycle life, offering you various capacities to meet more of your requirements.

TUV Certified · CEC accredited · IP65 Protection · Flexible Expansion

BLUESUN SOLAR CO.,LTD.

Tel: +86 (158) 5821 3997 | Fax: +86 (551) 6565 2651 | E-mail: info@bluesunpv.com
Add: 1499 Zhenxing Road, Shushan District, 230031 Hefei, China



*Release BLUESUN Battery Series-2024-07-Rev01-EN